



GENERAL SPECIFICATIONS

• L.O.A	49' 2"
• Hull length	49' 2"
• L.W.L.	43' 6"
• Beam	14' 6"
• Light displacement Deep keel	28,914 lbs
• Air draft Standard	73' 4"
• Standard keel Cast iron	7' 10"
• Standard keel ballast	10,516 lbs
• Deep keel Lead / Cast iron (optional)	9' 2"
• Deep keel ballast	9,480 lbs
• Freshwater capacity	143 gal
• Fuel oil tank capacity	63 gal
• Engine power	75 HP sail drive

ARCHITECTS / DESIGNERS

• Architect Naval	P. Briand Yacht Design
• Architecture Interior	Veerle Battiau

EC CERTIFICATE

- Category A - 8 persons
- Category B - 9 persons
- Category C - 14 persons

CLASSIC MAST DIMENSIONS AND AREA

• Mainsail (classic)	738,4 sq/ft
• Genoa (max)	754,55 sq/ft
• Spinnaker	1722,23 sq/ft
• I	62' 5"
• J	17' 7"
• P	60' 8"
• E	21' 3"

STANDARD MAST DIMENSIONS CARBON (OPTIONAL)

• Mainsail (classic)	802,99 sq/ft
• Genoa (max)	819,13 sq/ft
• Spinnaker	1722,23 sq/ft
• I	65' 9"
• J	50' 5"
• P	63' 12"
• E	21' 4"



STANDARD EQUIPMENT

CONSTRUCTION

Design made following European Directive requirements and according to EC certification.

- Monolithic hull design in polyester
- Monolithic structural hull liner laminated and bonded to the hull
- Injection moulded deck (Sandwich / Glass fiber / Balsa wood / Synthetic resin)
- All deck and work access area surfaces are non-slip
- Monolithic deck counter moulding cemented to deck
- Deck hull join banded and screwed, with 1 solid wood toerail:
- Standard keel - torpedo type bulb shape - in cast iron / Cast iron keel body and bulb
- Deep keel (optional) - torpedo type bulb shape - mixed lead / cast iron / Lead bulb and hollow cast iron keel body and antimony
- The keel is fixed to the boat by a system of screws and stainless steel washers
- Rudder, foam core with glass fibre and polyurethane - Injection moulded stock - Self-aligning rocker bearings with race bearings and rollers
- White colored hull - Grey hull decoration

DECK EQUIPMENT

RIGGING

- Standard 9/10 electro-polished aluminum mast, 3 sets of spreaders keel stepped
- Socket fitting - 2 Collar tie rods - 10 Blocks
- 3 Retractable steps
- Anodised aluminum boom max depth
- Kicking strap hydraulic
- Standing rigging ROD
- Single backstay - Hydraulic piston adjusted
- Standard fore stay - Plate fixed in chain locker
- Genoa furler - Drum under deck
- 1 Mainsail sheet track at bottom of cockpit
- 2 Genoa sheet tracks - Ball bearing genoa car adjustable under tension - 2 Track end fittings with lead blocks for back and forth control - 2 Genoa sheet return blocks - 2 Clutches on deck for the back and forth with plates and blocks - 3 Furling line blocks - Lead - Jammer
- Complete running rigging Dyneema®: 1 Genoa halyard - 1 Genoa furler line - 2 Genoa sheets - 2 Back and forth Genoa traveller - 1 Main halyard - 1 Mainsail foot - 1 Mainsail sheet in cockpit - 3 reef lines
- 12 Jammers
- 2 5 sheaves cheek blocks at mast level
- 2 Deck organiser on the deck house
- Spinnaker pre-rigging and fittings: 2 Spinnaker sheet plates - 2 Spinnaker arm plates - 2 Spinnaker pole down haul plates

WINCHES

Aluminum Harken winches self-tailing:

- 1 Mainsail H50.2 STA winch on cockpit centre mounting
- 2 Rigging winches H50.2 STA on deck house
- 2 Genoa sheet winches 60.2 STA on cockpit coamings
- 2 Winch handles

BOW - MOORING - ANCHORING

- 1 Stainless steel bow fitting - Asymmetric spinnaker tack point
- 2 Lockable covers with separate opening
- Self-bailing chain locker with clenche eye
- Retractable bow roller system, gas piston assisted - Anchoring (Anchor Soc 52 lbs 40M of 0' 5" diameter chain, 40M of 0' 7" diameter rope)

- 1500 W Vertical electrical windlass - Breaker - Relay box 12 V - Remote control with wire - Swivel bow roller
- Sail locker
- 6 Aluminum mooring cleats - Stainless steel guards bolted to dock hull join

DECK SECURITY

- 2 stainless steel pulpit(s)
- 2 Stainless steel aft pushpits - 1 Central pulpit - linked by 2 opening lifelines with snap shackles
- Lifelines with double adjusting turnbuckles, Stainless steel stanchions and bases
- Side opening in port and starboard lifelines
- Flag pole mountings - Ring lifebuoy bracket
- 2 Compound handrails fitted to deck by side porthole covers
- 2 Jointed plates for harness (companionway and on mainsail mounting)

COCKPIT

- Self-bailing cockpit
- 1 Locker under each cockpit bench
- 1 Halyard locker at companionway
- 1 Rope and mooring line locker in cockpit sole - Gas piston lid
- 1 Compartment, aft of steering station to port
- 1 Gas cylinder locker, aft of steering station to starboard
- 1 Life raft locker in cockpit bottom - Gas piston lid
- Cockpit bench seats - Cockpit bottom and navigator seating decked in natural solid wood
- 2 Steering wheel consoles in lacquered aluminum: 2 Black lacquered aluminum steering wheels, imitation carbon covered (900 mm diameter) - 2 Steering Gear - Chain and metal cable transmission linked to sector
- 1 Emergency tiller
- 2 Navigation compasses encased in catwalks forward of steering stations
- Engine control and instrument panel at end of starboard cockpit bench
- Spaces for navigation electronics (optional extra) recessed into port and starboard cockpit benches
- 2 Waterproof speakers
- 2 parts entrance door in PMMA (Storage under companionway) - 1 Sliding hatch made of PMMA

AFT TRANSOM

- Reclining stern deck / Swim deck - Natural solid wood decked
- Opening of stern deck with gas piston assisted manual tackle
- 1 Stainless steel swimming ladder
- 1 Cockpit shower hot/cold water

FITTINGS

- Light colored Alpi woodwork
- Parquet type laminated floors

COMPANIONWAY

- Headroom: 6' 7"
- Stainless steel companionway - Moulded wood steps with non-slip surface - Removable
- 2 Stainless steel handrails

FORWARD CABIN

- Headroom: 6' 3"
- Central double bed Island berth (6'7" x 4'11") - Marine mattress - Lathed bed base - Padded bedstead
- Hanging locker - 2 Drawers - Storage cupboard - glove boxes - 1 Dressing table - Cubbyholes along the hull
- 1 Deck hatch with mosquito net (1 Step under spar ceiling for emergency exit)
- 2 Fixed hull portholes

FORE WASHROOM

- Headroom: 6' 5"
- Washroom moulded in one piece to be watertight
- Separate shower - Shower - Mixer tap - Shower door in PPMA
- Manual marine toilet - Seat
- 1 Rigid sewage tank (21gal)
- Countertop with square synthetic resin washbasin with mixer tap and stainless steel beading
- Storage cupboard with drawer - Closed cubbyholes
- Toilet accessories: Paper dispenser - Rubbish bin
- 2 Mirrors
- 1 Opening deck hatch with shutter

SALOON

- Headroom: 6' 5" - 6' 7"
- L-shaped bench seat - double density foam
- 1 Rectangular salon table - Solid wood frame - Handhold - Central storage - 2 Stainless steel legs
- 2 Removable seats - Stainless steel legs - matching saloon
- Starboard sofa bench
- Closed cubbyholes - Storage under bench seats - Storage under floor
- Leather covered stainless steel handrails under coamings
- 3 Opening deck hatches with blind / mosquito nets
- 2 Fixed hull portholes
- 1 Permanent ventilation system

GALLEY TO STARBOARD

- Headroom: 6' 7"
- T-shaped kitchen
- Countertop in varnished wood and synthetic resin - Solid wood beading - Handrails
- Rectangular sink - 1 Stainless steel basin - Mixer tap - 1 Closed drain rack
- 1 gas 2 burners on gimbals - Seat / Wooden worktop
- 1 Front opening evaporator fridge - 12 V - 3,5 cu/ft- Storage baskets
- 1 Cool box top opening - 12 V - 2,1 cu/ft
- Kitchen accessories: Cutting board - Rubbish bin - Sponge holder - Draining rack Stainless steel
- Closed cubbyholes - Storage - Storage cupboard with drawers - Drawers - Cutlery drawer - bottle holder
- Leather covered stainless steel handrails under coamings
- 4 opening portholes with blinds on coaming

CHART TABLE TO PORT

- Headroom: 6' 7"
- L-shaped chart table desk, (4' 7" x 4' 7") Space for charts and navigation instruments along the hull - Space for office / Computer facing companionway
- 1 Adjustable swivel navigator seat in PVC - Stainless steel legs
- Electrical panel - Access to charger and to electrical connexion
- Navigation instrument panel fitted in closed cubbyholes
- Player DVD - 2 Speakers in saloon - 2 Speakers in the cockpit TV 20" LCD
- Closed cubbyholes - glove boxes - Storage
- Handhold - Leather covered stainless steel handrails under coamings
- 1 Leather covered stainless steel hand rail on partition Aft washroom
- 2 opening portholes with blinds on coaming
- 1 White/red light fitting

PORT AFT WASHROOM

- Headroom: 6' 6"
- Washroom moulded in one piece to be watertight
- Shower tray - Shower - Mixer tap
- Manual marine toilet
- Countertop with square synthetic resin washbasin, Mixer tap - Stainless steel beading
- Storage cupboard with drawer - Closed cubbyholes
- Toilet accessories: Paper dispenser - Rubbish bin
- 2 Mirrors
- 2 Opening portholes with blinds on coaming

AFT CABIN

- Headroom: 6' 6"
- More space in port cabin than in starboard
- 2 Cabins each with:
 - 1 Double bed (To port 6' 7" x 4' 7" / 3' 11" - To starboard 6' 7" x 4' 1" / 3' 7") - Marine mattress
 - Backrest chair with armrest in hull
 - PVC hanger closets on stainless steel rails - 1 Drawer - Storage - glove boxes
 - 1 Opening porthole with blind on coaming
 - 1 Porthole opening on cockpit with blind
 - 1 Fixed hull porthole

ENGINE

- Engine YANMAR Diesel 75 hp
- Reverser Sail Drive
- Engine control - Key ignition - Instrument panel in cockpit to starboard
- Engine compartment: Foam soundproofing - Ventilation: 1 air intake and 1 air outlet
- 1 Alternator 12 V / 80 Amperes
- 1 Rotomolded diesel oil tank, 63 gal (under starboard aft berth) - 1 Electronic gauge - Stop valve - 1 Lockable deck filler (starboard aft cockpit)
- Filters :Sea water - Diesel - Decanter
- Foldaway three-blade propeller
- 1 Engine access through companionway - 2 Engine access panels aft cabins

ELECTRICITY

- 12 V circuit - 110 V circuit
- 2 service batteries (140 Amperes) - 1 110 Amperes engine battery - Battery switch
- 1 Charger 40 Amperes - 1 220 shore power - Charge divider
- Electrical panel backlit (12 V / 110 V) (Circuit breakers - Voltmeter 12 V / 110 V - Ammeter - Water gauge - Fuel gauge - Battery warning - Fuel warning - Water warning)
- 1 12 V Outlet - 7 110 V outlets
- Interior lighting LED: Adjustable wall-mounted luminaires and reading lamps - Indirect lighting
- Navigation lights LED: Navigation and anchor lights on mast - Port/ starboard prow light on pulpit - Sternlight on pushpit
- Wire runs for options cables

PLUMBING

- 2 Rotomolded freshwater tanks (87 gal Under forward berth - 63 gal under port aft berth) - Deck fillers - Tank selection with ¼ turn valves
- Waterpressure system - Expansion tank - Inline filter
- 11 gal Electric water heater (operation off engine or on 110 V electrical system)
- 1 Rigid waste tank (21 gal)
- Electrical shower drain pumps
- 1 Electric bilge pump - 1 Manual bilge pump

GAS

- 2 Tanks storage in cockpit sole (max diameter: 0' 11" x 1' 5")
- Supply system in copper - Regulator and solenoid

TRIM LEVEL

	DYNAMIC	AMBITION
1 Port electric manœuvring winch Harken 50.2 STAEH	■	■
Retractable wood and aluminum cockpit table	■	■
Leather seat and chart table blotting pad Moka	■	■
Leather bag and tool kit	■	■
Speakers ACOUSTIMASS® 3	■	■
3 hob oven/grill cooker on deluxe mounting	■	■
Electric quiet flush toilet forward and aft	■	■
Rigid sewage tank (21 gal) Aft toilet	■	■
2 140 amperes additional service batteries	■	■
2 Spinnaker sheet winches Harken 48.2 STA		■
1 Electric winch for mainsail sheet Harken 53.2 STAEH		■
Microwave oven		■
Shore freshwater supply		■

OPTIONS

PACKS

PACK ELECTRONIC RAYMARINE

Cockpit:

- 2 Displays (colors) TFT ST70 (Loch - Speedometer - Depth finder - Windvane - Anemometer)
- Multifunction screen E120 color 12.1" (GPS, chart plotter, Cartography chart mapper Navionics Gold, supplied without chart)
- Pilot SPX ST70 - LS 50 + Integrated gyrocompass - Control console

Mast foot:

- 3 Displays (colors) 6.5" ST70+ - Controls in the cockpit

PACK EASY DOCKING

- Bow thruster retractable
- 4 Mooring rope kit - 6 Fenders

OTHER OPTIONS

- Control Smartcontroller RAYMARINE
- Receiver AIS RAYMARINE
- VHF RAYMARINE 240 E
- Radar (radome only) RAYMARINE

- Grey colored hull - Anthracite grey hull decoration
 - Mast aluminum and Boom black lacquered (ROD)
 - White lacquered carbon mast, Track ronstan (ROD)
 - 2 Electric genoa sheet winches Harken 60.2 STAEH
 - 2 Genoa sheet winches Harken 70.2 STA
 - Electrical manœuvring winch - To starboard H50.2 STAEH
 - Symmetrical spinnaker rigging - Carbon spinnaker pole
 - Asymmetric spinnaker rigging
 - Track Facslide - Bearing sliders
 - Releasable fore stay - Turnbuckle - Runner and tackle
 - Lazy Jack kit
 - Natural solid wood lathed deck
 - Grey deck house hood
 - Grey cockpit cushions
-
- Double berth in saloon
 - Porthole screens
 - Crockery kit marked
 - TV aerial
 - Heating
 - Air conditioning
 - Inverter 12 V / 110 V - 2000 VA
 - 5.5 KVA Generator