



1 forward cabin - 1 Toilet, 2 Aft cabins - 1 Toilet



1 forward cabin - 1 Toilet, 1 Aft cabin - 1 Toilet

## GENERAL SPECIFICATIONS

• L.O.A	47' 3"
• Hull length	44' 11"
• L.W.L.	40' 0"
• Beam	13' 11"
• Deep keel (min)	6' 9"
• Deep keel ballast	6,422 lbs
• Shallow keel (min)	5' 9"
• Shallow keel ballast	7,143 lbs
• Air draft (min)	62' 6"
• Light displacement	23,292 lbs
• Fuel tank capacity	53 gal
• Freshwater capacity	150 gal
• Engine power	75 HP

## ARCHITECTS / DESIGNERS

- Architect Naval : Berret Racoupeau Yacht Design
- Architecture Interior : Nauta Design

## EC CERTIFICATE

- Category A - 8 persons
- Category B - 9 persons
- Category C - 14 persons

## CLASSIC MAST DIMENSIONS AND AREA

• Mainsail	443,47 sq/ft
• Genoa	(140 %) 594,17 sq/ft
• Asymmetric spinnaker	1231,5 sq/ft
• I	53' 11"
• J	16' 5"
• P	49' 9"
• E	17' 5"

## STANDARD EQUIPMENT

### CONSTRUCTION

- Design made following European Directive requirements and according to EC certification
- Monolithic hull design in polyester
- Monolithic structural hull liner laminated and bonded to the hull
- Deck in balsa and glass fibre sandwich covered in «diamond point» type non-slip surface
- Deck hull join banded and screwed, with 1 solid wood toerail
- Cast iron keel fixed with bolts and stainless steel backing plates
- Rudder, foam core with glass compound stock
- White coloured hull - Hull decorated in pearl grey

### DECK EQUIPMENT

#### RIGGING

- Standard mast 9/10 electro-polished aluminum on deck stepped, 2 sets of spreaders
- Anodised aluminum boom
- Discontinuous stainless steel standing rigging
- Single backstay with turnbuckle
- Rigid boom vang
- Genoa furling system with drum on the deck
- Mainsail sheet track
- 2 genoa tracks with piston adjusted traveller cars - 2 Genoa sheet return blocks
- Rigging run back to cockpit (except boom topping lift)
- Complete running rigging: Main halyard, genoa halyard with clutch on mast and cleat, Boom topping lift with cleat on mast, Mainsheet, 2 Genoa sheets 2 roller reefing lines, 1 manual reef
- 10 Jammers
- 6 Jamming cleats

#### WINCHES

- 2 Self-tailing genoa sheet winches (H50.2 STC)
- 2 Self-tailing manoeuvring winches (H40.2 STC)
- 2 Winch handles aluminum
- 2 Winch handle holders

#### SAILS

- Furling genoa with UV protective strip
- Semi full batten written sail with slider and roller slider
- Lazy Jack and Easy bag in Perle colour

#### MOORING - ANCHORING

- Self-bailing chain locker - Clench bolt - Hatch cover
- Stainless steel bow fitting 2 rollers
- 12 V - 1000 W Vertical electrical windlass - Remote control
- 6 Aluminum mooring cleats - Stainless steel dock line protection

#### DECK SECURITY

- 1 Open stainless steel forward pulpit - Step
- 2 Stainless steel aft pushpits
- 1 Ring lifebuoy bracket
- 1 Outboard engine bracket
- 1 Flag pole socket
- Double lifelines and stainless steel stanchions - Opening to port and to starboard in guardrail
- 2 Stainless steel handrails

### COCKPIT

- Self-bailing cockpit
- 1 Port cockpit locker
- 2 Lockers under helm seat
- 1 Gas locker for 2 bottles in cockpit sole
- Natural solid wood slatted cockpit benches
- 2 Steering wheel consoles: Stainless steel steering wheels - 2' 11" diameter - Leather covered - Rudder mechanism with metal cable transmission system - Stainless steel handrail - Navigation instrument pod (optional instruments)
- 1 Deck plate for access to tiller system
- 1 Emergency tiller
- 2 Steering compasses on consoles
- Engine throttle and control panel to starboard
- Polyester cockpit table - 2 leaves- Glove boxes - Central bottle holder - Bottle holder on reverse side - Stainless steel hand rail - 12 V socket - Lamp with shade
- 2 Waterproof speakers
- 2 Companionway doors in solid wood hinged - Sliding hatch made of PMMA

### AFT TRANSOM

- Access door pivoted on pantograph (Patented)
- Natural solid wood decking on sun deck
- 1 Life-raft locker in upper stern - 2 doors
- 1 Stainless steel swimming ladder - Solid wood steps
- 1 Cockpit shower cold/hot water
- 1 Shore power inlet

### FITTINGS

- Light colored Alpi Mahogany
- Parquet type laminated floors
- Deck and hull counter moulding covered with vinyl fabric spar ceiling

### COMPANIONWAY

- Headroom: 6' 6"
- Wooden companionway with hung steps in moulded wood with non-slip surface
- 4 Stainless steel handrails

### FORWARD CABIN

- Headroom: 6' 5"
- Central double bed (6' 7" x 6' 3"), Marine mattress
- Hanging locker, Cupboard and glove boxes
- 1 Sideboard to starboard
- 2 Hull portholes with curtain
- 2 Opening deck hatches with blind / mosquito nets

### FORE WASHROOM

- Headroom: 6' 5"
- Washroom moulded in one piece to be watertight
- Separate shower, shower mixer tap cold/hot water
- Manual marine toilet
- Washbasin - Synthetic resin countertop, Mixing tap cold/hot water
- Mirror
- Toilet accessories: Glass holder, Soap tray, Towel rail, Rubbish bin, Paper dispenser
- Cupboard and cubby hole
- 1 Opening deck hatch with shutter / mosquito net

## SALOON

- Headroom: 6' 4"
- Ushaped saloon bench, double density foam
- Salon table 1piece, Varnished wood top with inlay, Aluminum legs
- 2 persons bench seat with central foldaway armrest
- 4 Matching decorative cushions
- Cupboards, Cubby hole lockers and storage along the hull, Storage under bench seats
- 1 Panoramique window with pleated blind
- 2 Hull portholes with curtain
- 2 Fixed deckhouse side windows with pleated blinds
- 1 Porthole opening onto coaming in the starboard side window
- 3 Opening deck hatches with blind / mosquito nets

## CHART TABLE

- Control panel with hinged door - glove boxes - Storage - Moulded wood beading
- Navigator seat with cushion
- Pivoting electrical panel enabling access to electrical connections
- Navigation instrument panel (without instruments)
- Radio CD player / Stereo MP3 - 2 speakers
- 1 White light fitting / Red
- Stainless steel handrail on partition

## GALLEY

- Headroom: 6' 5"
- U-shaped kitchen fitted into companionway
- Synthetic resin countertop
- 1 Stainless steel sink 2 rectangular basins - Cutting board
- 1 Mixer tap cold/hot water
- 1 Gas 2 burners stove, stainless steel oven on gimbals, Stainless steel protection handrail
- 1 34 gal refrigerator, 12 V Refrigeration unit, front opening
- 1 26 gal ice box, top opening
- 1 Cutlery drawer
- Fitted cupboards and lockers (shelves, stainless steel basin on slider, tea towel holder, rubbish bin, bottle holder)
- 1 Opening porthole with curtain

## STARBOARD AFT WASHROOM

- Headroom: 6' 9"
- Washroom moulded in one piece to be watertight
- Separate shower, shower mixer tap cold/hot water - 2 doors shower cabinet made of PMMA
- Manual marine toilet
- 1 Rigid waste tank 21 gal
- Washbasin - Synthetic resin countertop, Mixing tap cold/hot water
- Mirror
- Toilet accessories: Glass holder, Soap tray, Towel rail, Rubbish bin, Paper dispenser
- Cupboard and cubby hole
- 1 Fitted deckhouse side window with curtain
- 1 Opening porthole with curtain

## AFT CABINS

### Version 1 aft cabin

- Headroom: 6' 9"
- Diagonal double bed (6' 7"x 5' 3"), Marine mattress
- Hanging locker, Cupboards, Lockers and cubby holes
- 1 Dressing table
- 1 Removable seat
- 2 Hull portholes with curtain
- 2 Opening portholes with curtain
- 2 Portholes opening onto cockpit with curtain
- 2 Opening deck hatches with blind / mosquito nets

### Version 2 aft cabins

2 Symmetrical cabins each one consisting of:

- Headroom: 6' 9"
- Double bed (6' 7" x 4' 11"), Marine mattress
- Hanging locker, Lockers and cubby holes
- 1 Hull porthole with curtain
- 1 Opening porthole with curtain
- 1 Porthole opening onto cockpit with curtain
- 1 Opening deck hatch with shutter / mosquito net
- Access door to aft washroom in starboard cabin

## ENGINE

- Engine Yanmar Diesel 75 hp
- Engine control - Instrument panel in cockpit
- Engine compartment: Foam soundproofing - Ventilation: 1 air intake and 1 air outlet
- 1 Alternator 12 V / 80 Ah
- 1 Rotomolded diesel tank 53 gal (under starboard aft berth) - Electronic gauge - Low level alarm - 1 Deck filler
- Filters: Sea water - Diesel - Decanter
- Stainless steel shaft - Polyester guard moulded into hull
- Fixed three blade propeller
- 1 Engine access through companionway (opening with gas piston)
- 2 Engine access panels aft cabins

## ELECTRICITY

- 12 V circuit - 110 V circuit
- 2 Service batteries (2x160 Ah) - 1 Engine battery (90 Ah)
- 1 40 Ah Battery charger - 1 110V shore power - 1 Isolator
- Electrical panel (12 V / 110 V) (Circuit breakers - Voltmeter - Water gauge - Fuel gauge - Battery warning - Fuel warning)
- 2 12 V Outlet - 7 110 V Outlets
- Lighting: Halogen ceiling lights, Reading lights, White/red light fitting
- Navigation lights: 1 Forward and aft navigation lights - 1 Engine navigation light / Foredeck light - 1 Anchor light on masthead - 1 Deck light
- Wire runs for options cables

## PLUMBING

- 2 Rotomolded freshwater tanks (53 gal port aft cabin - 87 gal forward cabin) - 2 Deck fillers - Separate tank filling - Tank selection with ¼ turn valves
- Waterpressure system - Accumulator tank - Inline filter
- 10 gal Electric water heater (Operation off engine or on 110 V electrical system)
- 1 Rigid waste tank 21 gal
- Delayed shower draining and electric shower drain pumps
- 2 Electric bilge pumps - 1 Manual bilge pump
- 1 Electric ice box drain pump

## GAS

- 2 Tanks storage in cockpit sole
- Regulator and solenoid